

- MAIN ROADS
- INDUSTRIAL AREAS
- ACCESS AND MINOR ROADS
- PEDESTRIAN PRECINCTS
- CITY SQUARES



**DISCERA BASYS 400** catenary suspended fitting with suspension bracket. Housing made of pressure die-cast aluminium, aluminium, stainless steel, toughened glass, stainless steel threaded inserts for regularly used fixing positions, stainless steel screws, wire bracket of galvanised steel, painted, features tool-free easy maintenance access with flush one hand operated lock, E-Block can be replaced without tools, asymmetric high performance mini-road reflector optics- VARIO-OPTIC for all layouts, for planning assistance please contact selux, Ø: 400mm, H: 132mm, protection category IP66, protection class I with option class II, adjustable tilt and orientation, with two cable glands for loop in-and-out, standard colour: silver (RAL 9006) [-3].

A<sub>w</sub>: 0,04 m², weight: 10 kg

**Catenary fixture SX 288** ■ ■ ■



**VARIO-OPTIC**

Mirror optics  
**asymmetric**



Mirror optics  
**symmetric**

**HST**

50W → **1 0**  
LVK → 7322

70W → **1 2**  
LVK → 7322

50W → **2 0**  
LVK → 7323

70W → **2 2**  
LVK → 7323

**HIT-CE\***


35W → **1 1**  
LVK → 7320

70W → **1 3**  
LVK → 7320

100W → **1 5**  
LVK → 7320

35W → **2 1**  
LVK → 7321

70W → **2 3**  
LVK → 7321



**DISCERA BASYS 600** catenary suspended fitting with suspension-bracket.

Housing made of die-cast aluminium, aluminium, stainless steel, toughened glass, stainless steel threaded inserts for regularly used fixing positions, stainless steel screws, wire bracket of galvanised steel, painted, features tool-free easy maintenance access with flush one hand operated locks, E-Block can be replaced without tools, asymmetric high performance mirror optics - VARIO-OPTIC for all layouts, for planning assistance please contact selux, Ø: 600mm, H: 171mm, protection category IP66, protection class I with option class II, adjustable tilt and orientation, with two

cable glands for loop in-and-out, standard colour: silver (RAL 9006) [-3].

A<sub>w</sub>: 0,07 m², weight: 12 kg

**Catenary fixture SX 289** ■ ■ ■



**VARIO-OPTIC**

Mirror optics  
**asymmetric**

**HST**

50W → **1 2**  
LVK → 7311

70W → **1 8**  
LVK → 7311

100W → **1 4**  
LVK → 7311

150W → **1 6**  
LVK → 7311

**HIT-CE**

70W → **1 3**  
LVK → 7310


100W → **1 5**  
LVK → 7310

150W → **1 7**  
LVK → 7310

**HIT-COS\***

60W → **4 3**  
LVK → 7310

140W → **4 7**  
LVK → 7310



\*G12 base • \*PGZ12 base for Philips CosmoPolis (HIT-COS).

Please complete reference no. with the relevant codes for optic, lamp and colour.

**Specification example:** **DISCERA BASYS 400 SX 288** ■ ■ ■ **asym., HIT-CE 35W\*** ■ **silver** ■

**Colour code:** → ■ silver (RAL 9006) **- 3**, choice of colours **- 9**

